

# marantz®

## SD4050 Dual Well Cassette Deck

- Autoreverse Twin-deck Design Allows Continuous Play and Record (Deck B) from One Loaded Tape to Another
- Super-Hard Permalloy Heads and Anti-resonant Front Panel Ensure Faithful Reproduction with Wide Dynamic Range and Minimal Wow and Flutter
- Peak Level Read-out, Fine Bias Tuning and Syncro Start of Tape and CD Ensure Accurate and Professional Style Home Recordings
- One-touch Dubbing with Hi-speed Option
- Dolby B/C Noise Reduction and Dolby HX-Pro for Low Noise and Extended High Frequency Response
- Manual Recording Level Allows User Adjustment
- Pitch Control for Changing Key and Tempo
- Timer Option for Unattended Recording



### FEATURES

Transport	2
Auto Reverse	•
DC Servo Control	•
Super-Hard Permalloy Head	•
2-Speed Syncro Reverse Dubbing	•
Automatic Tape Selector	•
Dolby HX-Pro	•
Noise Reduction	Dolby B & C
Quick Music Search	•
Auto Continuous Play	•
Timer Record & Play	•

### IN/OUTPUTS

AUDIO	
Analog L&R In (Line In)	1
Analog L&R Out (Line Out)	1
Headphone Out	1

### SPECIFICATIONS

AUDIO SECTION	
S/N Ratio	74 dB (3% THD)
Recording Bias	100kHz
Frequency Response (+/- 3 dB)	25Hz - 18kHz
Channel Separation	40 dB
Wow & Flutter	< 0.09%

### GENERAL

Color	Black
Front Panel	Brushed Plastic
Remote Control	RC455SD
Power Requirements	AC 120V 60Hz
Power Consumption	16W
Dimension W x H x D (Inches)	17 <sup>1</sup> / <sub>16</sub> " x 4 <sup>9</sup> / <sub>16</sub> " x 11 <sup>1</sup> / <sub>16</sub> "
Weight (lbs.)	8.8



\*All specifications, dimensions and weights are subject to change without notice. D&M Holdings, Marantz, Marantz America, Inc. or any of its subsidiaries will not assume any liability for errors within this document.